



Customer code:	NONE	Part number:	2.4-KF2D	Rev:	A	Changing log			
----------------	------	--------------	----------	------	---	--------------	--	--	--

Rev.	ECN#	Description	Changed by	Date
A	NONE	FIRST RELEASE.	Guangqiang.zhao	2025.08.09

NOTE:  
 1. ELECTRICAL CHARACTERISTICS:  
 1.1 FREQUENCY RANGE:DC~50GHz  
 1.2 IMPEDANCE:50Ω  
 1.3 VSWR:1.3 MAX (Design Assurance) .  
 1.4 INSERTION LOSS:≤0.05√fdB.  
 1.5 INSULATION RESISTANCE: 1000MΩ  
 1.6 DIELECTRIC WITHSTAND VOLTAGE:500V.  
 2. MECHANICAL CHARACTERISTICS:  
 2.1 DURABILITY: 500 CYCLES MIN.  
 3. ENVIRONMENTAL CHARACTERISTICS:  
 3.1 TEMPERATURE RANGE: -55°C~+125°C  
 3.2 ALL MATERIALS AND PROCESS ARE RoHS COMPLIANT.



DETAIL:A SCALE:3:1

③	CONTACT	COPPER ALLOY	GOLD	1EA
②	INSULATOR	ENGINEERING PLASTICS	NATURE	1EA
①	BODY	STAINLESS STEEL	PASSIVATION	1EA
ITEM	NAME	MATERIAL	TREATMENT	QTY
Bill Of Material				

TOLERANCES UNLESS OTHERWISE SPECIFIED		
ONE PLACE DECIMAL	.X	±0.2
TWO PLACE DECIMAL	.XX	±0.10
THREE PLACE DECIMAL	.XXX	±0.05
HOLE DIA. VARIATION	.XX	N/A
ANGULAR DIMENSION		±0.5°

Signature		Shinto P/N: 2.4-KF2D	
Approved By:		Description: 2.4 Female Vertical solderless	
Checked By:		Material: See BOM	Treatment: See BOM
Drawn By:		Unit: mm	Size: A4
		Scale: 5:1	Sheet: 1 of 1

**SHINTO** SHINTO ELECTRONICS CO.,LTD  
<http://www.shinto-electronics.com>